





FEATURES / APPLICATION	WINBUY #	DESCRIPTION
<p>DB 9 Pin (male) to DB 25 Pin (female), (6')</p> <ul style="list-style-type: none"> 9 Pin to 25 Pin conversion cable 	400725	<p>9 PIN (male) to 25 PIN (female)</p> 
<p>DB 9 Pin (male) to DB 9 Pin (female), (6')</p> <ul style="list-style-type: none"> Commonly used from Laptop to test at Pair Gain (HDSL) Wired straight 	400720	<p>9 PIN (male) to 9 PIN (female)</p> 
<p>DB 25 Pin (male) to DB 25 Pin (female), (6')</p> <ul style="list-style-type: none"> Standard Serial Printer Cable, (25 Wires) 	400706	<p>25 PIN (male) to 25 PIN (female)</p> 
<p>DB 9 Pin (female) to 25 Pin (male), (6')</p> <ul style="list-style-type: none"> IBM AT COM1 Computer Cable 	400703	<p>9 PIN (female) to 25 PIN (male)</p> 
<p>HDSL Provisioning Test Cord</p> <ul style="list-style-type: none"> DB 25 Pin (male) to DB 9 Pin (male) for HDSL provisioning from "Dumb" terminals 	<p>400703H10 (10') 400703H25 (25')</p>	<p>HDSL PROVISIONING TEST CORD</p> 